



## **Rheology Solutions**

*Rheology Solutions is the sole Australian distributor of this product range and we welcome the opportunity of discussing your application requirements.*

*We hope the information you are seeking is contained within this file.  
If you have any questions, or require further information please contact us.  
We look forward to being of further service.*

*Regards from the Team at Rheology Solutions.*

**RHEOLOGY SOLUTIONS PTY LTD.** ACN 082 479 632

**HEAD OFFICE:** 15-19 Hillside Street, Bacchus Marsh, Victoria 3340 Australia. PO Box 754, Bacchus Marsh, Victoria 3340 Australia.

**Telephone:** +61 3 5367 7477 **Facsimile:** +61 3 5367 6477 **Email:** [info@rheologysolutions.com](mailto:info@rheologysolutions.com) **Website:** [www.rheologysolutions.com](http://www.rheologysolutions.com)

# Thermo Scientific GLACIER Series Ultra-Low Refrigerated Circulators


## Glacier ultra-low refrigerated circulators

are suitable for external temperature applications with simultaneous operation in the bath tank. These circulators deliver high heating and cooling capacities for rapid heat-up and cool-down times.

Fitted with adjustable castors, drainport, and handles – it's a perfect fit for any environment. A heated top plate prevents condensation and icing at low temperatures.

## Typical applications:

- Jacketed reaction vessels
- Material testing
- Analytical instrumentation
- Calibration
- Condensers
- Crystalization



## Step 2



**Now select your bath below.**

To see all thermostat specifications, please refer to Page 3

Model		G50 ultra-low refrigerated circulator
Temp range	SC100	—
Dimensions (WxHxL) mm	thermostat	—
Temp range	SC150	-28 to 150°C
Dimensions (WxHxL) mm	thermostat	810 x 415 x 550
Temp range	SC150L	-28 to 150°C
Dimensions (WxHxL) mm	thermostat	810 x 415 x 550
Temp range	AC150	—
Dimensions (WxHxL) mm	thermostat	—
Temp range	AC200	-50 to 200°C
Dimensions (WxHxL) mm	thermostat	850 x 415 x 550
Bath capacity (Liters)		10-13
Cooling capacity at 20°		900W
Reservoir dimensions (DxWxL) mm		200 x 285 x 200
Net Weight (kg)		53

Ordering Information: Find the part number by matching the thermostat to the bath size and voltage you need				
Model		G50 ultra-low refrigerated circulator		
Voltages		208V/60Hz <sup>1,3</sup>	230V/50Hz <sup>1</sup>	200V/50-60Hz <sup>1</sup>
SC100 thermostat	Order no.	—	—	—
SC150 thermostat	Order no.	153-6509	153-6501	153-6507
SC150L thermostat	Order no.	154-6509	154-6501	154-6507
AC150 thermostat	Order no.	—	—	—
AC200 thermostat	Order no.	156-6509	156-6501	156-6507

*\*Bath volume varies depending on the fluid used, temperature range, and items inserted into the reservoir.*

Certification: <sup>1</sup>CE <sup>2</sup>cUL<sup>us</sup> <sup>3</sup>cRU<sup>us</sup>

Visit <http://www.ul.com/global/eng/pages/> to view the UL listings for Thermo Fisher Scientific. Reference file #E164214 for these products.